

**PATENT
5589-1045**

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

SCANNER PROJECTION SYSTEM

Inventor: **Loi Han**
1117 S. Valencia Street
Alhambra, California 91801
Citizen of United States of America

Wen Shu ("Bonny") Chen
9F-2, No. 472 Section 1
Kwang Fu Road
Hsinchu, Taiwan 30077
Citizen of Taiwan R.O.C.

Yu-Cheng Sheng
6303 Ridgepath Ct.
Rancho Palos Verdes, California 90275
Citizen of Taiwan R.O.C.

Attorneys:

Jon E. Hokanson
Brian Drazich
Thomas M. Small
Small Larkin, LLP
10940 Wilshire Boulevard
Eighteenth Floor
Los Angeles, California 90024
Tel. (310) 209-4400
Fax (310) 209-4450

5

Background of the Invention

A. Field of the Invention

10

The present invention is directed to a stand alone, flat bed scanner which incorporates removable digital storage media such as a floppy disk, disk drive or similar portable data storage media; a battery power supply; a central processing unit; a pivotal handle; an automatic document feed capability; and/or capability to output directly to a printer, a television screen and/or a multimedia projector.

B. Related Application

15

This Application incorporates by reference all of the subject matter set forth in commonly owned U.S. Patent No. 5,907,413, issued May 25, 1999 entitled "Contact Image Sensor Flatbed Scanner", and commonly owned U.S. application for patent Serial No. 09/436,712, entitled "Scanner With Removable Data Storage Media", filed November 9, 1999.

20

C. Description of the Prior Art

Stand alone, flatbed scanners and portable, hand-held scanners are known. Also, use of a removable digital data storage device, such as a floppy disk, in conjunction with a digital camera is known, such as found in the Sony brand, Mavica digital camera.

25

However, it is not known to include a central processing unit, removable storage media, portable capability, automatic document feed capability and/or the capability to output data

5 to a liquid crystal display (LCD) multimedia projector, which in turn may then project the data onto a screen.

Objects and Summary of the Invention

10 It is an object of the present invention to provide a scanner that incorporates a removable digital data storage media.

It is a further object of the present invention to provide a stand alone, scanner incorporating a 3.5 inch floppy diskette as a removable digital data storage media.

It is also an object of the present invention to provide a reflective/transmissive scanner incorporating a removable digital data storage media.

15 It is also an object of the present invention to provide a portable, hand-held scanner incorporating a removable digital data storage media such as a 3.5 inch floppy diskette.

It is a further object of the present invention to provide a CCD or CIS scanner having as an option, a removable digital data storage media such as a 3.5 inch floppy diskette, a Zip-Drive, CD Rom, or the equivalent.

20 It is a further object of the present invention to provide a flat bed scanner including a central processing unit for controlling scanning functions, and to provide the capability of output directly to a printer, to a television monitor, to a computer network and/or to an LCD projector.

25 It is a further object of the present invention to provide a stand alone flat bed scanner having an internal power supply, such as a rechargeable battery.

5 It is a further object of the present invention to provide a stand alone scanner having a handle for portable use.

 With reference to the above-described objects, the present invention provides a scanner of the type used as a stand-alone computer peripheral, but in combination with a removable digital data storage medium such as a 3.5 inch floppy diskette, a Zip-Drive®, or
10 the equivalent portable data storage media. Incorporation of a portable digital data storage media directly in the scanner eliminates the need to have a computer operatively connected to the scanner during the scanning process, i.e., conversion of an object image into digital data signals. With the present invention, an object image may be converted into digital data, stored in the portable memory media, and the portable memory may be removed from
15 the scanner, to be used subsequently and in digital processing equipment not operatively connected to the scanner which obtained the image.

 The present invention also provides a stand alone scanner that may include a central processing unit, and software adapted to control the scanning, editing, input and output functions related to the scanning process. The stand alone scanner alternate embodiments
20 of the present invention include not only removable digital data storage media, but also provide for output of the digital data directly to a printer, directly to a television screen, directly to a computer network and/or directly to an LCD projector. In one embodiment of the present invention, a built-in power supply and a carrying handle are provided so that the stand-alone scanner may be easily carried and be used in environments where no external
25 power supply is available. The stand-alone embodiments of the present invention may use CPUs of different capacity, with more advanced functions being available using higher

5 level CPUs, and having greater memory capacity.

Brief Description of the Drawings

Figure 1 is a perspective view of a first preferred embodiment of the present invention.

10

Figure 2 is a perspective view of a second preferred embodiment of the present invention.

Figure 3 is a perspective view of a third preferred embodiment of the present invention.

15

Figure 4 is a plan view of a first alternate preferred control panel for the present invention.

20

Figure 5 is a flow chart illustrating programming steps for use of the present invention.

Figure 6 is a perspective view of a fourth preferred embodiment of the present invention.

25

5 **Figure 7** is a front perspective view of the fourth preferred embodiment of the present invention with the cover in a partially open position.

Figure 8 is a first side view of the fourth preferred embodiment of the present invention with the cover partially open.

10 **Figure 9** is an enlarged top view of the control panel of the fourth preferred embodiment of the present invention.

15 **Figure 10** is a perspective view of the fifth preferred embodiment of the present invention.

Figure 11 is an exploded perspective view of the fifth preferred embodiment of the present invention.

20 **Figure 12** is a top perspective view of the sixth preferred embodiment of the present invention.

Figure 13 is a top view of the sixth preferred embodiment of the present invention.

25 **Figure 14** is a front side view of the sixth preferred embodiment of the present invention.

5 **Figure 15** is a rear view of the sixth preferred embodiment of the present invention.

Figure 16 is an exploded perspective view of the sixth preferred embodiment of the present invention.

10 **Figure 17** is a schematic drawing of the seventh preferred embodiment of the present invention scanner projection system.

Figure 18 is a rear view of a multimedia projector showing various inputs that may be used in conjunction with a scanner projection system of the present invention.

15 **Figure 19A** is an illustration of a remote control pointer device that enables the scanner of the present scanner projection system to interact with the multimedia projector.

Figure 19B shows the bottom view of the Figure 19A remote control pointing device.

20

Figure 20 illustrates a typical connection between the scanner and the multimedia projector of the present scanner projection system.

25 **Figure 21** is a flow chart illustrating programming steps used in the present scanner projection system during operation.

5 **Figure 22** is a flow chart illustrating various programming steps used in changing the scaling factor for the size of the image displayed during use of the present scanner projection system invention.

10 **Figure 23** is a schematic view of an eighth embodiment of the present invention, showing a stand alone CPU unit adapted for receiving direct output from a stand alone scanner, and providing input for video, for an LCD projector and providing for remote control.

Description of the Preferred Embodiments

15 Referring to Figures 1 through 25, several preferred embodiments of the present invention will be described. The present invention is directed to stand-alone, computer peripheral scanners which, in their conventional form, include a connection to and requirement that they be operatively connected to a computer for processing digital signals sent by either the charged couple device ("CCD") or a contact image sensor ("CIS")

20 incorporated within the scanner. The digital signals are then processed in the computer, and stored in a conventional storage media, such as a removable hard drive, 3.5 inch floppy disk, Zip-Drive® or the equivalent. The present invention is directed to incorporation of removable, or portable data storage media, i.e., memory, within the scanner itself. The present invention, therefore, enables the user to scan an image with, and store the digital

25 data representation of the image in, a portable memory in the scanner itself, and eliminates the need for having a computer operatively connected thereto during the scanning process.

5 The scanned image may then be stored on the portable memory, such as a 3.5 inch floppy disk, for example. The disk then may be removed from the scanner upon completion of scanning, and may be taken to a remote computer for further processing.

Referring to Figure 1, a first preferred embodiment of the present invention is shown, including a conventional CCD-type flatbed scanner 20, housing 22, glass platen 24
10 and hinged lid 26. Also shown at 28 is a disk drive into which a conventional 3.5 inch floppy diskette 30 may be inserted for storage of digital data generated during the scanning process. Also shown on the scanner housing is control panel 32, which will be described in greater detail in conjunction with Figures 3 and 4.

Referring to Figure 2, a second preferred embodiment of the invention is shown
15 adapted for use in a CIS-type scanner 34. The scanner 34 includes a housing 36, glass platen 38, hinged cover 42, and a CIS scanner positioned on a carriage 40. A CIS scanner of this type is described in commonly owned U.S. Patent No. 5,907,413, incorporated by reference as if set forth fully herein. Housing 36 also incorporates a conventional disk drive, such as a disk drive 44 for a conventional 3.5 inch floppy disk 46.

Referring to Figure 3, a third preferred embodiment is shown, including a
20 conventional transmissive/ reflective type scanner 50, a housing 52, reflective scanning platen 56 and a transparency holder 54. This type of transmissive/reflective scanner is of the type disclosed in commonly owned U.S. Patent No. 5,705,805, entitled Transmissive/ Reflective Optical Scanning Apparatus; commonly owned U.S. Patent No. 5,814,809
25 entitled Transmissive/Reflective Optical Scanning Apparatus and in commonly owned U.S. Patent No. 5,574,274. Referring to Figure 3, scanner 50 also incorporates a conventional

5 disk drive into which a removable conventional, preferably, formatted, 3.5 inch floppy
diskette 58 may be used for purposes of the present invention. The housing 52 includes a
control panel 60 which includes a liquid crystal display 62 ("LCD") and a multi-function
control button 64.

Referring to Figure 4, an alternate control panel 66 is shown having LCD display
10 68 and a plurality of control buttons. Control button 70 controls the mode of operation,
either color, or black and white, with the light emitting diode ("LED") 72, when energized
indicating the color mode of operation. The black and white mode of operation is indicated
when LED 74 energized. Control button 78 controls the resolution of the scanner, with a
high, low and medium resolutions preferred. LED's 80, 82 and 84 indicate whether the
15 selected resolution is high, low or medium, respectively. Control button 86 is for
controlling whether the LCD display is "on" or "off", the "on" being indicated simply by
having an image on the display 68, and "off" being indicated by an absence of a display.
Control button 88 is the erase control button, in which case an image stored in the disk
drive may be erased. Control button 76 controls advance of the image displayed to the next
20 image stored in the media. Button 90 controls the data compression of raw data.

Alternatively, and as shown in Figure 3, the alternate control panel 60, control
panel includes a multi-function control button 64 with "left", "right", "up", "down", and
"enter" control functions, as is conventional. With such a multi-function control button 64,
the various operational control choices are displayed as a series of menus on the LCD 62,
25 with a cursor or pointer being controlled by operator movement of the multi-function
button.

5 Referring to Figures 1 through 4 above, the present invention scanner provides for either reflective or transmissive scanning, and flatbed or handheld scanning, as is conventional and, at various resolutions, as also is conventional. However, the present invention also provides for transfer of the digital data representative of each scanned image directly to a portable memory positioned in the scanner itself. Alternatively, of course, an
10 alternate transfer path may be incorporated into the scanner whereby digital data may be transferred directly to a computer, as is found in conventional scanners of this type.

Preferably the portable memory incorporated into a scanner of the present invention is a 3.5 inch floppy diskette, as is well known. Also, the present invention may be used in conjunction with other types of conventional data storage media, such as a flash memory
15 card (also known as a PCMCIA card); a 100 MB Zip-Drive; a 120 MB, 3.5-inch diskette using a 120 MB, 3.5-inch disk drive available from O.R. Technology, Campbell, California, as its model FD-3120A (drive has industry standard ATAPI IDE interface); and also may be adapted to use a compact disk (CD) with write capability. The conventional 3.5 inch floppy diskette holds approximately 1.44 megabytes of data, which is equivalent to
20 approximately 30 to 40 images, after compression, for a standard resolution, color VGA, 640 X 480 pixel image.

With respect to a standard or normal resolution for flatbed scanners of the general type described herein, a 300 dots per inch ("dpi") resolution is typical. At this resolution, using a color mode of operation, it is expected that a conventional 3.5 inch floppy diskette
25 would store approximately 10 to 12 images wherein the object is of a standard letter size, i.e., 8½ x 11 inches, with presently available data compression technology.

5 Also, as will be appreciated, incorporation of a portable storage media such as a floppy diskette, etc., will require adaptations to the scanner such as provision for a battery and AC power supply to the memory device. With respect to the different types of portable storage media, a 3.5 inch floppy disk is most preferred, with a Zip-Drive, holding approximately 100 megabytes of data, being also preferred.

10 Referring to Figure 5, a flow chart of programming steps for controlling the data collection, display and storage features of the invention will be described. Each of the blocks in the block diagram represent a programming step, or a series of programming steps which are available as conventional software, and/or readily generated using conventional programming techniques. Control routine 92 begins by starting the function
15 at step 94 at the conventional on/off power button, not illustrated in Figure 4. Once the system is energized, the mode of operation is selected at step 96, being either a color or black and white mode of operation. As shown in Figure 4, control step 96 is selected with button 70, and LED 72 indicating a color mode of operation and LED 74 indicating a black and white mode of operation. Once the mode of operation is selected, the degree of
20 resolution is selected, at step 98. Corresponding control button 78, with high 80, medium 82 and low 84 resolution LEDs also shown on the front of the control panel in Figure 4. With conventional scanners, the medium resolution is typically 300 dpi, a high resolution is typically 600 dpi, with as high as 1200 dpi. For scanner operation, a low resolution is typically approximately 100 dpi.

25 Once the resolution has been selected, the scanning function is begun, at step 100, during which the carriage is advanced across the length dimension of the scanner to scan

5 the object image and, through a CCD or CIS camera the object image is converted into digital data representative of the object image. Referring to Figure 4, the scan or advance control button is shown at 76. Once the data has been scanned, data may be compressed, in step 102, using a conventional data compression routine, such as JPEG, or the equivalent. It is within the scope of the present invention that a single, predetermined data compression routine may be incorporated into the computer software application program controlling the operation of the scanner, or that several data compression options may be available, with further control options made available at the control panel (not shown) for selecting a particular data compression technique. Once the data has been compressed, it is then stored on the removable digital data storage media, step 104 indicating being stored on disk. Alternatively, no data compression is also an option, step 103. Data Compression is controlled by button 90, as shown on Figure 4. Once the data has been stored on the disk, it may also be displayed on the LCD display, step 106, corresponding to display 62 (Figure 3) or display 68 shown at Figure 4. The stored data may be erased as described above in conjunction with control button 88.

20 Referring to Figures 6-9, a fourth preferred embodiment 200 of the present invention is a conventional flat bed scanner that incorporates a personal computer (PC) central processing unit (CPU) underneath the scanner platen and adapted to control conventional scanning, editing, input and output functions. The PC CPU is not shown in Figures 6-9, but can be conveniently positioned within the housing of the scanner, preferably underneath the platen of the scanner. The scanner 200 includes a top cover 202 and a housing 204. The front of the scanner includes a control panel 206 which is

5 preferably flush with the level of the scanner which includes the platen. The shape, style and overall external configuration of the scanner may take many forms, one preferable form of which is illustrated in Figures 6-9. Referring to Figure 7, the scanner 200 is shown with its cover 202 in a partially raised position, exposing a recess 210 that is configured and adapted for use as a handle to raise and lower the cover. The top surface of
10 the scanner housing includes a scanning bed 212 having a conventional glass platen. The front of the scanner includes a conventional 3.5" floppy disk drive 214 and a conventional 100 MB drive 216, commonly referred to as a "Zip®" brand drive. Both of these drives are operatively connected to the CPU in a conventional fashion.

Referring to Figure 8, this preferred embodiment also, preferably includes a
15 conventional share port 218, a conventional printer port 220 and a conventional accessory port 222 for use, optionally, for peripherals such as a document feeder.

With reference to Figure 9, the control panel 206 includes controls and indicators for numerous functions used during operation of the scanner. Start button 226 initiates the selected operation, such as scan, or copy, both of which are conventional functions in
20 scanners, as is well known. Stop/clear button 228 controls and permits the current scanner function to be stopped during operation. This function is used for printer set up operations and to return any settings back to default values. Also, pressing and holding the stop/clear button 228, preferably for 5 seconds, will reset a conventional file name counter. Mode button 230 functions to toggle between copying images to a connected printer, which may
25 be either black and white or color, and scanning to a floppy or Zip® disk, which may be black and white, gray scale or color. The desired operation is selected, preferably, by

5 pressing the mode button repeatedly to cycle through the various options. Compression
button 232 functions to choose the amount of file compression desired for the scanned
image. The options included, preferably, are low, medium and high compression.
Conventional compression techniques are used in the present invention. As is well known,
lower compression results in a larger file size but provides better image quality. In the
10 preferred embodiment, compression setting is not available for the copy function or when
scanning in a black and white mode. The control panel also includes the +/- button 234,
with the - function illustrated at 236 and the + function illustrated at 238. These buttons
function to specify the number of pages to be printed, when the scanner is in the copy mode
of operation. When the scanner is in scan mode, these buttons function to increase or
15 decrease the resolution level. Also, when the mode button 230 is pressed and held for at
least 5 seconds, preferably, and with the printer mode selection selected, the +/- buttons
234, 236 and 238 function to choose a printer mode number that corresponds to a printer
model. Various printer models are supported, as desired, with the present invention.

Resolution control button 240 functions to choose the level of detail desired for a
20 particular image to be scanned. The resolution is increased by using the + button 238 and
decreased by pressing the - button 236. The preferred resolution settings for the scan
function, in dots per inch, for the default settings for low, medium and high resolution are
as follows:

In black and white mode: 150, 300 and 600

25 In gray scale: 75, 150 and 300.

In color: 75, 150 and 300.

5 In the copy function the resolution settings, in dots per inch, the default settings for low, medium and high resolution are as follows:

 In black and white: 300, 450 and 600.

 In color mode: 100, 150 and 300.

10 In this preferred embodiment of the present invention, the settings shown on the LED display panel during the copy mode refer not to the resolution setting itself but rather to the number of copies to be printed.

 Scan area selection button 242 functions to choose the maximum size that can be scanned by the scanner. In the present invention, the preferred sizes are A4, which is 8.5" by 11.7"; and letter, which 8.5" by 11" and "auto". Auto refers to enablement of an
15 automatic edge detection system, which is conventional. In this mode, the scanner will complete an initial pass to find the edges of the photo or document and then scan only the detected area. When using this mode, it is preferable to keep the lid closed.

 The document function button 244 functions to automatically set preferred defaults
20 for quickly scanning a text document. In the present invention, the preferred default settings are B/W for the scan mode. Although in this mode color documents may be scanned, the resulting output would be black and white. The default resolution is 300 dpi, the scan area is letter size and no compression is performed. After the document button is pressed to select the default settings, individual settings may be altered as desired, and then
25 scanning may be started by pressing the start button 226.

 The "save to" button 246 functions to select whether the scanned images are saved

5 to a Zip® disk or to a floppy disk. In the present invention, it is preferred that pressing and holding the "save to" button for at least 5 seconds will cause the CPU to attempt to format the floppy disk into an IBM-compatible formatted disk. This function will erase all files on the disk unless it is write protected. Various file formats may be used, but in the present invention the PCX file format is preferred for files scanned in black and white mode, and
10 Jpeg file format is preferred for files scanned in the color mode.

Also, preferably, saved files are assigned numeric file names in sequence, starting from img01.pcx or img01.jpg, repeating after img99. Preferably, the counter may be reset back to img01 by pressing and holding the stop/clear button 228 for at least 5 seconds. In this case the LED display will show "F1" to indicate that the counter has been reset to
15 indicate file number "1".

Although the present invention could use an internal clock, the preferred embodiment does not and all saved files are date stamped as January 1, 1999.

Various indicator lights and labels may also be used on the control panel 206. For example, in the preferred embodiment, indicator lights 248 and 250 indicate B/W and
20 Color, respectively in the copy mode. Indicator lights 252, 254 and 256 indicate B/W, Gray and Color, respectively in the scan mode. Indicator lights 258, 260 and 262 indicate high compression, medium compression and low compression, respectively.

Above the LED 263 display, indicator lights 264, 266 and 268 indicate an
25 unformatted disk, a full disk and no disk, respectively. Above, the resolution button 240, indicator lights 270, 272 and 274 indicate high resolution, medium resolution and low

5 resolution, respectively. Above the scan area control button 242, indicator lights 276, 278 and 280 indicate A4, letter and auto sizes respectively. Above the "save to" control button 246 the indicator lights 282 and 284 indicate selection of the Zip® drive or diskette, respectively.

10 This fourth preferred embodiment of the present invention is a 36-bit, stand-alone scanning appliance with scan, copy, image-saving, image-compression and disk-formatting capabilities combined into a single scanner. This preferred embodiment is a stand-alone scanner which means that there is no need to connect the scanner to a computer. Rather, once power is supplied to the scanner, it is ready to scan and copy, save and perform its other functions. Because it is a stand alone scanning device, it comes with its own file
15 saving features built in. The Iomega brand Zip® drive accommodates a standard 100-MB, IBM-compatible, formatted Iomega Zip® disk and also includes a standard floppy drive that accommodates conventional 3.5" floppy disks. This preferred embodiment includes 600 x 600 dpi optical resolution and scans in color, gray scale and black and white modes. Also, preferably, it is adapted for and may include conventional image editing, document
20 management, and OCR software for scanning photos and documents, thus making the entire scanning process simple and convenient.

Typical optional uses for the present invention would include the scanner to scan images and then send the scanned images to a printer. In this configuration, a standard printer cable from the printer's parallel port is preferably connected to the present
25 invention's printer port 220. Then, the "mode" control button 252 is held for at least 5 seconds, and the +/- keys are operated to choose the printer mode number corresponding

5 to the printer model that is connected. The start button is then pressed to save the printer mode number into the computer's CPU memory and set up is complete.

In an alternate mode of operation, the same printer may be shared with a PC and the scanner of the present invention. In this application two standard parallel printer cables are used, with one cable connected from the printer to the printer port 220 and the second
10 printer cable connected from the PC's parallel port to the "share port" 218 shown in Figure 8. During operation in this mode, the scanner of the present invention must be turned "on".

In yet another mode of operation, the scanner of the present invention may be configured to work with Microtek brand, standard 10-page auto document feeder, such as
15 model ADF-600L, for simplified multi-page document scanning. In this mode of operation, the upper lid 210 is removed by raising it up 90° and lifting it straight up. Then the metal posts of the ADF are inserted into the holes on the right side of the scanning bed, shown at 288 and 290 in Figure 7. The ADF is then plugged into the accessory port 222 in the scanner, and is ready for automatic document feed mode.

20 The present invention also includes numerous conventional warning indicators that are displayed on the LED display panel. Detection processing and display of these indicators are conventional, and may include messages such as "write-protected disk", "no-disk", "disk full", "disk not formatted", "warm up" and so forth, as is conventional.

25 Described below are several operations of the present invention.

5

Scan And Save A Color Photo

In this operation, a color photo is scanned and saved to a floppy disk in a format suitable for on-screen display. The steps, including operator steps and steps performed by the CPU scanner are as follows:

1. Turn the scanner on.
- 10 2. Place the photo to be scanned face down on the scanner glass, and close the scanner lid.
3. Press the mode button 230 repeatedly until the green LED light goes on in the scan section of the panel and then choose "color".
4. Insert a 3.5" IBM-compatible formatted disk into the floppy drive 214.
- 15 5. Press the "save to" button 246 to select "floppy".
6. Set the resolution button 240 to "low" (75 dpi) and set the compression control button 232 to "high" to create the smallest file size.
7. Press the scan area button 242 repeatedly until "auto" is selected.
8. To start scanning, press start button 226. The image will then be scanned
- 20 and saved to the diskette, with the file format such as img01.jpg. The document can then be opened for viewing in an image-editing software program on the computer with conventional image-editing software such as Ulead® PhotoImpact brand software.

25

Scan And Save A Test Document

In this mode of operation, a printed page of text is scanned and then saved to a

5 floppy disk in the format suitable for OCR (optical character recognition) text processing.

The steps are as follows:

1. Turn the scanner on.
2. Place the document face down on the scanner platen 212 with the top of the page on the left side of the scan bed and close the scanner lid.
- 10 3. Press the document control button 244 to set default values for various settings.
4. Insert a 3.5" IBM-compatible, formatted disk into the floppy drive 214.
5. Press the start button 226 to begin scanning and saving the document. It will be saved with a file name such as img01.pcx. The file can later be opened for OCR processing in conventional software such as Caere PageKeeper
15 Standard or Caere Omni Page Limited Edition.

Copy (Print) An Image To The Printer

In the copy/print an image to the printer mode of operation, a photograph is copied by printing it on a color printer. The printer must be properly connected to the scanner and the correct printer mode must be selected on the scanner. The steps for performing this operation are as follows:

1. Turn the scanner on.
2. Place the photo face down on the scanner platen 212, and close the scanner
25 lid 202.
3. Press the mode control button 230 repeatedly until the green LED light goes

- 5 on in the scan section on the panel and choose "color".
4. Press the resolution button 240 and choose "low".
 5. Press the scan area button 242 and choose "auto".
 6. Press the "+" or the "-" button to indicate the number of copies to be printed.
 - 10 7. Press the start button 226. The image is then scanned and sent as a copy to the printer.

Fifth Preferred Embodiment

With reference to Figures 10-11, a fifth preferred embodiment 300 of the present invention will be described. The fifth preferred embodiment also includes, internally, a CPU and is similar in many respects to the fourth preferred embodiment described above, 15 except that the fifth preferred embodiment is adapted to be portable; employs a contact image sensor (CIS) rather than a charged coupled device (CCD) sensor; includes additional memory; and/or is configured to display directly to a TV or VGA monitor.

The scanner 300 includes a housing 302, a lid 304 and a control panel 306. The lid 20 is hinged and the control panel is similar in appearance and function to that as described above with respect to the fourth preferred embodiment. The housing 302 includes provision for a floppy disk as well as a Zip® drive, although only one of these could be employed in a specific commercial embodiment. The housing 302 also includes a handle 308 which is pivotally fastened to the housing and when not in use, is pivoted to lie within 25 recess 310 which is shown in Figure 10. The fifth preferred embodiment also includes a memory module within its control circuitry, with preferably either a 4 Meg or 8 Meg

5 capacity, neither of which are shown but both of which are conventional.

Also, the scanner 300 is configured and adapted to display directly to a VGA monitor using conventional firmware and, also, is configured to output for display on a TV screen. In this later configuration, conventional CyberPro 2010 firmware available from IGS Technologies is preferably used. Also, the fifth preferred embodiment may include a
10 controller for use with the TV.

Referring to Figure 10, the scanner 300 housing 302 includes a front side 316, a back side 318, a left side 314 and a right side 312. Figure 11 is an exploded perspective view of the scanner 300 showing the lid 304, the intermediate panels, not numbered, and the pivotal handle 308, with one of the pivots illustrated at 320. The monorail for
15 movement of the CIS module is also shown at 322. The CPU and memory module are illustrated at 324 and 326, respectively.

The fifth preferred embodiment also is adapted for and contains a conventional rechargeable battery, such as a Lithium so that it may be used in situations when an external power supply is not available. The operation of the scanner 300 is similar to that as
20 described above, with respect to the fourth preferred embodiment, except that the images may be displayed directly on a television screen.

Sixth Preferred Embodiment

With reference to Figures 12-25 a sixth preferred embodiment 400 will be
25 described.

The fourth and fifth preferred embodiments of the present invention preferably use a

5 CPU of the "486" type and employ DOS based operating systems. The sixth preferred embodiment preferably uses a Pentium type CPU and employs a Windows '98 operating system with network capability.

The sixth preferred embodiment includes 600 dpi x 1200 dpi optical resolution using conventional scanning techniques. It is also networkable via the standard Ethernet
10 connection. The scanner also includes 12" x 17" reflective and a 9.5" x 11.5" transparency scan frames. Optionally, a conventional transparent media adapter may be used with the sixth preferred embodiment. The scanner 400 also includes full 36-bit color depth capability, employs, preferably, a 250 MB Iomega® Zip® internal disk drive and a 1.4 MB internal disk drive. The scanner 400 also includes a 10 GB hard drive, preferably.

15 The sixth preferred embodiment is adapted for commercial quick copy, quick print operations, corporate offices, libraries, schools and other multiple user environments. It has a large, A 3 (12" x 17") color scanning capability and LCD panel for quickly and easily stepping through a scanning process. The scanner 400 is adapted for rapid scanning by the novice of photos, illustrations or documents, relatively fast saving of files to Zip®
20 cartridges, the scanner's own internal hard drive, or transmitting the files over a network to a specific work station for later use.

The scanner 400 includes a lid 402, and a raised, arcuate handle 418 for raising the lid about the pivots, one of which is shown at 416. On the top of the housing a rotatable LCD display panel 404 is shown in the raised position. Conventional multi-function
25 control panel 406 provides for controls, with corresponding instructions and indications provided on the screen of the LCD panel 404. The scanner 400 includes a front face 408, a

5 right side 410, left side 412 and a back side 414. Referring to Figure 13, the lid 402, handle 418, LCD panel 404 and control panel 406 are shown. In Figure 14, the arcuate configuration of the handle 418 is illustrated and the front of the Zip® drive 420 and floppy drive 422 are also shown in front side 408. Figure 15 illustrates the back side 414 and hinges 416 as well as the LCD panel 404, shown in a down position. Figure 16 is an exploded perspective view of the scanner 400 including the lid 402, the hinges 416, the LCD panel 404, the control panel 406, the scanning surface 424, the Zip® drive 420 and floppy drive 422.

15 The scanner 400 is a conventional, single pass color flat bed scanner that supports reflective and transparent scanning of originals that size from 35mm to 11 ½" x 9 ½". The preferred sensor in the scanner is a conventional tri-linear RGB CCD, 8000 elements per array. The LCD display is a conventional 5" diagonal LCD display. The illumination for the scanning is preferably a cold cathode fluorescent lamp. A conventional 5" diagonal LCD display is used for previewing and scanning and includes an 8-button navigational control panel, an Ethernet port, a keyboard port an additional VGA monitor, a TV monitor and an SCSI-2 port.

20 The bit depth, and color, is preferably 36-bit to optimize 24-bit and the gray scale is, preferably 12-bit to optimized 8-bit. Line art capability is 1-bit.

The preferred sample depth is 12 bits per color to 36 bits per color. The preferred dynamic range is RX:2.3 (D max) and TX:3.2 (D max).

25 It is estimated that the scanning time for a 4" x 5" object, scanned at 600 dpi, is 50

5 seconds. The maximum interpolated resolution is about 9,600 dpi and the maximum optical resolution is about 600 x 1200 dpi. The scanner employs a universal power supply with auto switching capability and may be operated at the voltage of 95 to 254 VAC. The scanner will operate in frequency of 50 hertz to 60 hertz at 110/240 volts. The maximum estimated power consumption is 200 watts.

10 In operation, the sixth embodiment is a stand alone scanner which can be used by simply plugging it into a conventional external power supply. Scanning takes place in a fashion similar to that as described above with respect to alternate embodiment for, except, of course that the scanning and storage capacities are larger, and the control is through a different, conventional control system.

15 The images may be scanned and saved directly to the internal disk drive, the Iomega® Zip® cartridge, a conventional 3.5" floppy disk, or transmitted via the Ethernet port and connected to an office or commercial environment network. Because the scanner includes a CPU it is a stand-alone color scanning station with images saved in formats readable by Windows or Macintosh operating systems. When connected to a network the
20 scanner operates like an image server, displaying recently scanned files for acquisition from any computer active on the network. Use of this scanner will free up other computers in the system otherwise tied up to scanning functions.

With the optional, conventional transparent media adapter, the sixth preferred embodiment is available for scanning film positives or negatives as large as 9.5" x 11.5".

25 Images may also be sent via e-mail over the network by use of a conventional, PC compatible keyboard. This scanner also features a conventional auto crop function which

5 determines the location of the original to be scanned on the bed and the crops right to its edges. The 5-inch diagonal LCD display measures 4" x 3".

Seventh Preferred Embodiment

10 With reference to Figures 17-22 a seventh preferred embodiment 500 will be described. In the seventh preferred embodiment, a stand alone scanner, of the type described above, having its own CPU, of type 486 or higher is used in a stand alone scanner 502. The scanner 502 has the capability for video output 504 to a television 506, as well as VGA or SVIDEO output 508. The VGA or SVIDEO output is directed to LCD projector 510, which in turn projects the scanned image onto screen 512.

15 In the seventh preferred embodiment, an infrared (IR) remote control 514 is used to control the scaling of the image projected on the screen 512 by use of a zoom out function 516 and/or zoom in function 518. Also, particular regions of the scanned image may be selected or centered, by using the left function 520, the up function 522, right function 524 and/or down function 526 controls on the IR remote control unit 514. The conventional enter function 528 and conventional escape function 530 may also be accessed via the IR remote control 514.

20 The scanner 502 schematically shown in Figure 17 with an object to be scanned 532 is shown in Figure 17. The scanner 502 also has a conventional start control 534. During operation, the seventh preferred embodiment includes placing the object to be scanned 532 on the glass platen, face down, pressing the start button 534. In the present invention, the start button 534 has been configured to enter a projection mode whereby the image scanned

5 will be projected onto the screen 512 via LCD projector 510 via a VGA or SVIDEO output 508. Once the entire image has been shown on the screen 512, the various control features of the remote control unit 514 may be used to change the scale of the image displayed on the screen and/or to browse different areas of the image scanned from object 532.

10 With reference to Figure 18, a typical rear view of LCD projector 510 is shown with various inputs and outputs. Two inputs, 536, 538, preferably DB-15 connections, are shown for use with computers. Two inputs 540, 542, preferably many-stereo connections, are shown for use in inputting audio from a computer. Two inputs 544, 546, preferably windows only DB-9 connections, are shown for use in receiving input via serial input from a mouse type pointing device. Input 548 is shown for a composite video source, preferably
15 an RCA type connection. Input 550 is shown as a S-VIDEO source, preferably a conventional S-VIDEO connection. Input 560 is shown as another audio input, preferably a mini-stereo connection.

Connections 562 and 564 are outputs for active, that is amplified, audio components, preferably mini-stereo connections. Connection 566 is an output for a video
20 monitor, preferably an RCA type connection. Connection 568 is an output for a CRT or LCD monitor, preferably a DB-15 type connection.

The projector 510 is a conventional multimedia projector that includes a projection lens, remote control mouse sensor, power cord connectors and a master power (on/off). The projector also includes a conventional air filter, control panel, a zoom lens capability,
25 the remote control mouse sensor, a projection lens, power cord connectors, carrying handle, and a lens cover. The main connection panel is located on the rear of the projector,

15

20

25

30

Table 2

Microtek Brand MVP 800x Projector

Resolution	True XGA with compression for 1.280 x 1.024 (SXGA)
Colors	16.7 million
Display Type	Three 1.3" 1.024 x 768 Polysilicon LCDs
Image Size	35-300"/89-762 cm. diagonal image
Video Compatibility	S-VIDEO, NTSC, PAL, SECAM
Data Compatibility	PC, Mac, SXGA, XGA, SVGA, VGA
Anti-Keystoning	Built-in 8.5 degree keystone correction
Projection Lens	1.35 x manual zoom and focus
Versatility	Front and rear
Loop-thru	Drives multiple projectors/External monitors
Audio	2 built-in stereo speakers, 3 watt peak output each
Lamp	150 watt UHE (Ultra High Efficiency)
EMI & Safety Certification	FCC-A, UL, C-Tick, cUL, CE/TUV, CNS
Lamp Life	2,000 hour life (average)
Dimensions	8" (197 mm.) Tall x 10" (257 mm.) Wide x 14" (360 mm.) deep
Weight	14.9 lbs/ 6.7 kg.
Power Requirements	90-240V, 50-60 Hz., autoranging, power loop-thru
Environment	Temperature: Operation: 5°C, 41° F-95°F Storage: -10°C to 60°C, 14°F-140°F Humidity: Operation: 20% to 80% Storage: 20% to 80%

With respect to the various modes of operation supported by these two projectors, Table 3 provides the relevant specifications.

Table 3

Supported Modes for Microtek MVP700s/800x

Mode Name(s) Used	Horiz. Res.	Vert. Res.	H(kHz)	V(Hz)
TV Video Modes				
NTSC TV Mode	700	525	15.7kHz	60
PAL TV mode	700	625	15.6kHz	50
VGA Modes				
VGA Text	720	400	37.9kHz	85Hz
VESA Modes				
VGA60	640	480	31.5khz	60Hz
VGA72	640	480	37.9kHz	72Hz
VGA75	640	480	37.5kHz	75Hz
VGA85	640	480	43.3kHz	85Hz
SVGA56	800	600	35.1kHz	56Hz
SVGA60	800	600	37.9kHz	60Hz
SVGA72	800	600	48.1kHz	72Hz
SVGA75	800	600	46.9kHz	75Hz
SVGA85	800	600	53.7kHz	85Hz
XGA60	1024	768	48.4kHz	60Hz
XGA70	1024	768	56.5kHz	70Hz
XGA75	1024	768	60.0kHz	75Hz
XGA85	1024	768	68.7kHz	85Hz
SXGA60*	1280	1024	64.0kHz	60Hz
MAC Modes				
Mac 13	640	480	35.0kHz	66.667Hz
Mac 16	832	624	49.7kHz	74.6Hz
Mac 19	1024	768	40.2kHz	74.94Hz
Mac 1960	1024	768	48.2kHz	59.28Hz
Mac 21*	1152	870	68.7kHz	75.06Hz

Both of these projectors include a conventional control panel, not shown. In the preferred embodiment projectors, the control panel is located on the top of the unit. As described above, these LCD projectors are of conventional design.

With reference to Figures 19A and 19B, the remote control 568 for the LCD projector 510 will be described. Figure 19A shows the top view of the controller 568. The controller 568 enables the user to interact with the projector 510 on projector 510's onscreen display and customize various operations. The remote controller also includes

5 features for the laser pointer and, when used with a Windows® based operating system,
functions as a remote mouse. The laser pointer is activated at laser pointer button 570.
The remote mouse curser button, which functions as a mouse curser when used with a
Windows® based operating system, is shown at 572. Left and right click mouse buttons
574 and 576, respectively, are also shown, for use as these functions when used with a
10 Windows® based operating system. Other conventional functions may be controlled by the
controller 568 with input button 578, mute control button 580, lamp control button 582,
menu selection control 584, channel increase control 586, enter function 588, volume
decrease control 590, channel decrease control 600, and volume increase control 602.

With reference to Figure 19B, the bottom view of the remote control 568 is shown.
15 IR transmitter 604 is shown at the top. Additional control button 606 is shown near the
middle of the remote control. Control 606 functions as does the left mouse click button for
a Windows® based system. Battery compartment 608 is shown near the lower part of the
controller.

With reference to Figure 20, a typical scanner projection system arrangement is
20 illustrated. In the Figure 20 schematic, a scanner 610 is shown with a VGA monitor cable
output 614. The scanner 610, as shown in Figure 20, may be any of the previously
described scanners, provided that they are stand alone scanners having a central processing
unit of at least a 486 capability, and having the adaptations as described elsewhere in the
specification, for providing output to an LCD type projector 510. The VGA monitor cable
25 614 are connected to the corresponding inputs 536, and 562, as described above, for the
LCD projector 510. In this regard, and in general, if the computer was connected to PC 1

5 in, the related connected channels should also be PC 1 audio in and mouse 1 input connectors. The connectors should not be connected across channels such as PC 1 in, PC 2 audio and so forth. In order to utilize the projector 510s internal, amplified stereo speakers, the preferred mini-stereo-to-mini-stereo audio cable should be connected to the appropriate PC 1 or PC 2 audio in connector at the rear of the projector 510. The other
10 end of the cable should be connected to the audio output connector of the IBM-compatible lap top or notebook computer.

If the remote mouse feature is desired for use with the multimedia projector's remote control mouse, then it is also necessary to connect to the serial mouse cable.

Referring to Figure 21, a flow chart 616 illustrating programming steps used in the present scanner projector system during operation will be described. Each of the blocks in
15 the flow chart 616 represent a software routine, or a series of software routines, which are available as conventional software, and/or readily generated using conventional programming techniques.

Image digital data processing commences with user selection of settings for the projector scan 618 as previously described and subsequent actuation by depression of the
20 scanner start button 620. Once the processing has commenced the scanner is calibrated by operation of one or a series of calibration routines 622. Following calibration one line of image digital data 624 is acquired by the digital camera and processed sequentially by one or a series of shading correction routines 626 and one or a series of DCR color and gamma
25 correction routines 628, following which the one line of image digital data is written to video memory 630.

5 If the line of image digital data written to video memory 630 is not the last line 632 of the image scan, the next line of image digital data is acquired and processed as aforesaid. This sequence of image digital data acquisition and processing steps is repeated line by line until the last line of the image scan has been acquired at 624, processed at 626 and at 628, and written to video memory at step 630.

10 As the lines of the image scan digital data are written to video memory 630, the image digital data stored in video memory 630 is projected onto the screen 512 via LCD projector 510 via a VGA or SVIDEO output 508. Once the completed image digital data have been stored and displayed, the image is available to the image browsing function 634 via one or a series of routines which permits user selection of the displayed image scale, 15 browsing and centering of any selected region of the display image 662, as further described.

Referring to Figure 22, flow chart 617 illustrating the various programming steps used in changing the scaling factor for the size of the image display and for browsing and/or centering a region of the displayed image will be described. Each diamond symbol 20 in the flow chart 617 represents a user operation of a key of the IR Remote Control 514 and each block represents a software routine, or a series of software routines, which are available as conventional software, and/or readily generated using conventional programming techniques. Changing the displayed image 662 is initiated by user depression of the various keys of the IR Remote Control 514. A software routine 636, or a series of 25 software routines, query whether a key of the IR Remote Control 514 is actuated. If a key of the IR Remote Control 514 is actuated a series of software routines 638, 640, 642, 644,

5 646 and 648 query which key has been actuated. If the IR Remote Control 514 up key 522 is actuated, software routine 638, or a series of software routines, initiate operation of software routine 650, or a series of software routines, to change the vertical position of the displayed image 662 pursuant to an algorithm of the type $Y1 \text{ equals } Y1 - ((480 * 4) / \text{ZOOMFACTOR} [\text{ZOOMSTATUS}])$ where Y represents the vertical axis, as is
10 conventional.

If the IR Remote Control 514 down key 526 is actuated, software routine 640, or a series of software routines, initiate operation of software routine 652 or a series of software routines, to change the vertical position of the displayed image 662 pursuant to an algorithm of the type $Y1 \text{ equals } Y1 + ((480 * 4) / \text{ZOOMFACTOR} [\text{ZOOMSTATUS}])$, where
15 Y again represents the vertical axis, as is conventional.

If the IR Remote Control of 514 right key 524 is actuated, software routine 642, or a series of software routines, initiates operation of software routine 654, or a series of software routines, to change the horizontal position of the displayed image 662 pursuant to an algorithm of the type $X1 \text{ equals } X1 + ((640 * 4) / \text{ZOOMFACTOR} [\text{ZOOMSTATUS}])$,
20 where X represents the horizontal axis, as is conventional.

If the IR Remote Control 514 left key 520 is actuated, software routine 644, or a series of software routines, initiates operation of software routine 656, or a series of software routines, to change the horizontal position of the displayed image 662 pursuant to an algorithm of the type $X1 \text{ equals } X1 - ((640 * 4) / \text{ZOOMFACTOR} [\text{ZOOMSTATUS}])$,
25 where X again represents the horizontal axis, as is conventional.

If the IR Remote Control 514 zoom in key 518 is actuated, software routine 646, or

5 a series of software routines, initiates operation of software routine 658, or a series of
software routines, to change the scale of the displayed image 662 pursuant to an algorithm
of the type which modifies the horizontal X1 and the vertical Y1 values of the displayed
image 662 and which further sets up a scaling factor for display of a smaller portion of the
image digital data stored in video memory 630 and displays a smaller portion of the stored
10 image digital data than previously displayed, resulting in enlargement of that portion of the
image which is displayed.

15 If the IR Remote Control 514 zoom out key 516 is actuated, software routine 648,
or a series of software routines, initiate operation of software routine 660, or a series of
software routines, to change the scale of the displayed image 662 pursuant to an algorithm
of the type which modifies the horizontal X1 and vertical Y1 values of the displayed image
662 and which further sets up a scaling factor for display of a larger portion of the image
digital data stored in video memory 630 and displays a larger portion of the stored image
than previously displayed, resulting in a reduction of that portion of the image which is
displayed.

Eighth Preferred Embodiment

20 Referring to Figure 23, an eighth preferred embodiment 666 of the present
invention is a stand alone central processing unit (CPU) operationally connected to and
adapted for receiving direct output 682 from a conventional stand alone scanner, and
providing input for display by video or by an LCD projector, as well as providing for
25 remote control. The stand alone CPU includes the housing 670 containing the central
processing unit operationally connected with conventional removable digital data storage

5 media 668 also contained within said housing 670. The housing also provides a plurality of control buttons, preferably located on the top surface of the housing, including a power (on/off) button 672, an erase function button 674, an advance next image control button 676, and a raw data compression button 678. The housing 670 also contains an infrared sensor 680 operationally connected to the central processing unit and removable digital data storage media which permits control via IR Remote Control unit 514 of the image displayed on the screen 512 by the LCD projector 510 through the VGA or SVIDEO output 508 from the central processing unit. Alternatively, the infrared remote control 514 may control the image displayed by a television monitor 506 to which the central processing unit is operationally connected via video output 504.

15 The image digital data processed by the central processing unit is written to video memory and stored on the removable digital data storage media 668 as previously described with respect to other preferred embodiments of the invention. In this embodiment, the preferred removable digital data storage media is a conventional 3.5 inch floppy disk, with a Zip-Drive, holding approximately 100 megabytes of data, being also preferred. The various control features of the IR Remote Control unit 514 together with the software algorithms previously described with respect to Figure 21 and Figure 22 may be used to change the scale of the image displayed upon the screen 512 or a television monitor 506 and/or to browse different areas of the image digital data.

25 It will be understood that certain features and subcombinations are of utility and may be employed without reference to other features and subcombinations as they are outlined within the description above and within the claims appended hereto. While the

- 5 preferred embodiments and application of the invention have been described, it is apparent to those skilled in the art that the objects and features of the present invention are only limited as set forth in the claims appended hereto.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2